



## Specifications Ansell LED Downlight Reef Matt White 5W 486lm 90D - 830-840-860 CCT | 85mm - IP65 - Adjustable - Outdoor

[View Product](#)

### General Information

|                          |                                       |
|--------------------------|---------------------------------------|
| SKU                      | 245366                                |
| EAN                      | 5056144245697                         |
| Brand                    | Ansell                                |
| Manufacturer Name        | Reef LED Adjustable Surface CCT White |
| Any Lamp all-in warranty | 3 Years                               |
| Average Lifetime (h)     | 54000                                 |

### Technical Information

|                             |                                                 |
|-----------------------------|-------------------------------------------------|
| Emergency Lighting          | No Emergency Unit                               |
| Tilttable                   | No                                              |
| Technology                  | LED Integrated                                  |
| Wattage                     | 5                                               |
| Voltage (V)                 | 220-240                                         |
| Dimmable                    | Not Dimmable                                    |
| Colour Code                 | 860 Daylight, 830 Warm White, 840 Cool White    |
| Colour temperature (Kelvin) | 6000 Daylight, 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                                           |
| Colour of Light             | White                                           |
| Light colour options        | CCT                                             |
| Including bulb              | Yes                                             |

|                          |                                       |
|--------------------------|---------------------------------------|
| Beam Angle (degree)      | 90                                    |
| Luminous Flux (Lumen)    | 486                                   |
| Luminous Efficacy (lm/W) | 97                                    |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | PC (Polycarbonate)                    |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                       |                    |
|-----------------------|--------------------|
| Mounting Method       | Surface            |
| Cut out (mm)          | 72                 |
| IP-rating             | IP65               |
| Operating Temperature | -20 to +40         |
| Housing               | PC (Polycarbonate) |
| Colour of the Fixture | White              |
| Colour of material    | White              |
| Fixture Connection    | Screw terminal     |
| Series                | Reef               |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 110 |
| Diameter (mm) | 85  |

## Sensor Information

## Why Any-lamp?

Type of sensor No Sensor

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process